

Material Safety Data Sheet

Slick Seam

Davis Instruments Corp

1.0 Manufacturer and Product ID

Manufacturer: Davis Instruments Corp.
3465 Diablo Avenue
Hayward CA 94545
510.732.9229

Product Number and Description: #730 Slick Seam
Chemical Name and Synonyms: N/A
Chemical Family: Petrolatum & Microcrystalline Wax NF
Formula: Proprietary

2.0 Hazardous Ingredients

Description	%	UNIT
None		

3.0 Physical Data

Parameter	Value
Boiling point:	NDA
Vapor Pressure:	NDA
Vapor Density (Air at Sea Level = 1):	NDA
Solubility in water:	Nil
Appearance and odor:	Soft, greenish-brown, non-aromatic wax.
Specific Gravity (H ₂ O = 1):	0.815-0.89 g/cc @ 60 °F
Percent volatile by volume:	0
Evaporation Rate (H ₂ = 1):	NDA
pH:	N/A

4.0 Fire and Explosion Data

Flash point: > 204 °C, > 410 °F (ASTM D-92)

Flammable limits: LEL: NDA UEL: NDA

Extinguishing media: Dry chemical, CO₂, foam, waterfog, sand/earth

Special fire fighting procedures: Water spray is unsuitable as an extinguishing agent. Firefighters should use self-contained breathing apparatus to protect against smoke inhalation.

Unusual fire and explosion hazards: None

5.0 Health Hazard Data

Threshold limit value: NDA

Effects of overexposure: NDA

Emergency first aid procedures: Eyes: Flush immediately with cold water. Contact a physician.
Skin: For molten Slick Seam, flush immediately with cold water.
Contact a physician. For solidified Slick Seam, remove excess with

Material Safety Data Sheet

Slick Seam

paper towels, wash with soap and water. Ingestion: Contact a physician.

6.0 Reactivity Data

Stability:	Stable
Incompatibility:	Keep away from flame, heat (250 °F max), and strong oxidizing agents.
Hazardous decomposition products:	Carbon monoxide and carbon dioxide are generated during combustion.
Hazardous polymerization:	Will not occur

7.0 Spill or Leak Procedure

Steps to be taken in case material is released or spilled:

Shut off leak and dike up large spills. After cooling and solidification, scrape and/or shovel up material. Finally, clean area with an oil-absorbent material.

Waste disposal method:

Dispose of in accordance with local, state, and federal regulations.

8.0 Special Protection

Respiratory protection:

NDA

Ventilation:

NDA

Protective gloves:

When molten, wear impervious gloves.

Eye protection:

When molten, wear face shield over protective glasses.

Other protective equipment:

When molten, wear coveralls.

9.0 Special Precautions

Precautions to be taken in handling and storage:

Store away from flame, heat (250 °F max), and strong oxidizing agents. Avoid skin and eye contact.

Other precautions:

None.