

**1 Identification of substance**

- Product details
- Trade name: Epifanes Nautiforte
- Application of the substance / the preparation Paint
- Manufacturer/Supplier:  
W.HEEREN & ZOON BV  
Postbus 166  
1430 AD Aalsmeer
- Information department: Environment protection department.
- Emergency information: Zie rubriek Fabrikant/leverancier

**2 Composition/Data on components**

- Chemical characterization
- Description:  
Resin mixture  
Solvent mixture with pigment additives

• Dangerous components:

64742-48-9	Naphtha (petroleum), hydrotreated heavy Xn; R 10-65-66	10-25%
64742-82-1	Naphtha (petroleum), hydrosulfurized heavy Xn; R 65	2.5-10%
96-29-7	2-butanone oxime Xn; R 21-40-41-43	≤ 2.5%
95-63-6	1,2,4-trimethylbenzene Xn, N; R 10-20-36/37/38-51/53	≤ 2.5%

- Additional information:  
For the wording of the listed risk phrases refer to section 16.

**3 Hazards identification**

- Hazard description: Not applicable.
- Information pertaining to particular dangers for man and environment:  
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.  
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.  
R 10 Flammable.  
R 66 Repeated exposure may cause skin dryness or cracking.
- Classification system:  
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.
- NFPA ratings (scale 0 - 4)  
Health = 2  
Fire = 2  
Reactivity = 0
- HMIS-ratings (scale 0 - 4)  
Health = \*2  
Fire = 2  
Reactivity = 0

Printing date 05/19/2005

Reviewed on 05/19/2005

Trade name: Epifanes Nautiforte

(Contd. of page 1)

**4 First aid measures**

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Seek medical treatment.

**5 Fire fighting measures**

- Suitable extinguishing agents:  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Protective equipment: Wear fully protective suit.

**6 Accidental release measures**

- Person-related safety precautions:  
Ensure adequate ventilation  
Wear protective equipment. Keep unprotected persons away.
- Measures for environmental protection:  
Do not allow to enter sewers/ surface or ground water.
- Measures for cleaning/collecting:  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.

**7 Handling and storage**

- Handling:
- Information for safe handling:  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- Information about protection against explosions and fires:  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- Storage:
- Requirements to be met by storerooms and receptacles:  
Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

**8 Exposure controls and personal protection**

- Additional information about design of technical systems:  
No further data; see item 7.
- Components with limit values that require monitoring at the workplace:  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information:  
The lists that were valid during the creation were used as basis.

(Contd. on page 3)

Trade name: Epifanes Nautiforte

(Contd. of page 2)

- Personal protective equipment:
- General protective and hygienic measures:  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.
- Breathing equipment:  
Suitable respiratory protective device recommended.  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- Protection of hands:  
Protective gloves  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material  
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection: Tightly sealed goggles

**9 Physical and chemical properties**

• General Information

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic

• Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

• Flash point: > 40°C (> 104°F)

• Ignition temperature: 240.0°C (464°F)

• Auto igniting: Product is not selfigniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

• Explosion limits:

Lower:	0.6 Vol %
Upper:	7.0 Vol %

• Vapor pressure at 20°C (68°F): 1.0 hPa (1 mm Hg)

• Density at 20°C (68°F): 1.190 g/cm<sup>3</sup>

• Solubility in / Miscibility with

Water:	Not miscible or difficult to mix.
--------	-----------------------------------

(Contd. on page 4)

Trade name: Epifanes Nautiforte

(Contd. of page 3)

- Viscosity:  
Kinematic at 20°C (68°F): 40 s (ISO 6 mm)
- Solvent content:  
Organic solvents: 22.7 %  
VOC content: 22.6 %  
270.3 g/l / 2.26 lb/gl
- Solids content: 49.1 % (VB% 1h150 C)

## 10 Stability and reactivity

- Thermal decomposition / conditions to be avoided:  
No decomposition if used according to specifications.
- Dangerous reactions No dangerous reactions known.
- Dangerous products of decomposition: No dangerous decomposition products known.

## 11 Toxicological information

- Acute toxicity:
- LD/LC50 values that are relevant for classification:

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)

96-29-7 2-butanone oxime

Oral	LD50	3700 mg/kg (rat)
Dermal	LD50	200-2000 mg/kg (rat)
Inhalative	LC50/4 h	20 mg/l (rat)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.

## 12 Ecological information

- General notes:  
Water hazard class 3 (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.

Trade name: Epifanes Nautiforte

(Contd. of page 4)

**13 Disposal considerations**

- Product:
- Recommendation:  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

\* **14 Transport information**

- DOT regulations:
- Hazard class: 3
- Identification number: UN1263
- Packing group: III
- Proper shipping name (technical name): PAINT
- Label: 3
- Land transport ADR/RID (cross-border):
- ADR/RID class: 3 Flammable liquids
- UN-Number: 1263
- Packaging group: III
- Description of goods: 1263 PAINT
- Maritime transport IMDG:
- IMDG Class: 3
- UN Number: 1263
- Label: 3
- Packaging group: III
- EMS Number: F-E, S-E
- Marine pollutant: No
- Proper shipping name: PAINT
- Air transport ICAO-TI and IATA-DGR:
- ICAO/IATA Class: 3
- UN/ID Number: 1263
- Label: 3
- Packaging group: III
- Proper shipping name: PAINT

\* **15 Regulations**

- Sara
- Section 355 (extremely hazardous substances):  
None of the ingredient is listed.
- Section 313 (Specific toxic chemical listings):

1330-20-7	xylene
95-63-6	1,2,4-trimethylbenzene
71-43-2	benzene

- TSCA (Toxic Substances Control Act):

13463-67-7	titanium dioxide
64742-48-9	Naphtha (petroleum), hydrotreated heavy
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy

(Contd. on page 6)

Trade name: Epifanes Nautiforte

(Contd. of page 5)

96-29-7	2-butanone oxime
136-52-7	cobalt bis(2-ethylhexanoate)
1330-20-7	xylene
68409-80-3	Isomeren van vetzuren calciumzouten, C6-C19 Isomers from fatty acid salts
95-63-6	1,2,4-trimethylbenzene
64742-95-6	Solvent naphtha (petroleum), light arom.
7778-18-9	calcium sulphate, natural
64742-88-7	Solvent naphtha (petroleum), medium aliph.
108-65-6	2-methoxy-1-methylethyl acetate
141-78-6	ethyl acetate
123-86-4	n-butyl acetate
112-34-5	2-(2-butoxyethoxy)ethanol

• Proposition 65

• Chemicals known to cause cancer:

1694-09-3	benzyl violet 4B
71-43-2	benzene

• Chemicals known to cause reproductive toxicity:

71-43-2	benzene
---------	---------

• Cancerogenity categories

• EPA (Environmental Protection Agency)

1330-20-7	xylene	D
71-43-2	benzene	A

• IARC (International Agency for Research on Cancer)

13463-67-7	titanium dioxide	3
136-52-7	cobalt bis(2-ethylhexanoate)	2B
1330-20-7	xylene	3
1694-09-3	benzyl violet 4B	2B
71-43-2	benzene	1

• NTP (National Toxicology Program)

71-43-2	benzene	K
---------	---------	---

• TLV (Threshold Limit Value established by ACGIH)

13463-67-7	titanium dioxide	A4
1330-20-7	xylene	A4
71-43-2	benzene	A1

• MAK (German Maximum Workplace Concentration)

96-29-7	2-butanone oxime	2
71-43-2	benzene	1

• NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7	titanium dioxide
71-43-2	benzene

• OSHA-Ca (Occupational Safety & Health Administration)

71-43-2	benzene
---------	---------

(Contd. on page 7)

Trade name: Epifanes Nautiforte

(Contd. of page 6)

- Product related hazard informations:  
The product has been classified and marked in accordance with directives on hazardous materials.
- Hazard-determining components of labelling:  
2-butanone oxime
- Risk phrases:  
10 Flammable.  
66 Repeated exposure may cause skin dryness or cracking.
- Safety phrases:  
2 Keep out of the reach of children.  
23 Do not breathe fumes/aerosol.  
24 Avoid contact with skin.  
46 If swallowed, seek medical advice immediately and show this container or label.  
51 Use only in well-ventilated areas.
- National regulations:
- Technical instructions (air):

Class	Share in %
I	≤ 2,5
NK	10-25

- Water hazard class:  
Water hazard class 3 (Self-assessment): extremely hazardous for water.

\* **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing MSDS: Environment protection department.
- Contact: J.J. van Dijk
- \* Data compared to the previous version altered.