

HWC G105, G129, G199, G505

HARVEY WESTBURY CORP.

HARVEY WESTBURY CORP.

18 B East 5th Street

Paterson, NJ 07524

(973) 684-0800

Fax: (973) 684-8009

MATERIAL SAFETY DATA SHEET

Product Code: 40629, 40162, 40163,
40164, 40168, 40169
Trade Name: Royal Satin Paste Wax
Proper Shipping Name: Polish Compound
Schedule B#: 3404.90.9100-7

Revision Date: 05/01/03
Supercedes Form: 03/07/97

HAZARDOUS INGREDIENTS

Materials/Components	% w/w	CAS No.	Hazard Data
Mineral Spirits	45-50%	8052-41-3	ACGIH: TLV 100 ppm OSHA: PEL 100 ppm
Morpholine	1.3%	110-91-8	ACGIH: TLV 20ppm STEL 30ppm OSHA: PEL 20 ppm (SKIN)
Crystalline Silica	2-5%	14464-46-1	ACGIH: TLV-TWA 0.1mg/m ³
Crystalline Silica	1-2%	1317-95-9	ACGIH: TLV-TWA 0.1mg/m ³
Quartz	1.3%	14808-60-7	ACGIH: TLV-TWA 0.1mg/m ³
Diatomaceous Earth	1-3%	68855-54-9	ACGIH: TLV 5mg/m ³

PHYSICAL PROPERTIES

BOILING POINT.....N/E
VAPOR PRESSURE.....N/E
VAPOR DENSITY (Air=1)...Heavier than air
WATER SOLUBILITY.. Water dispersible
APPEARANCE.....Beige Colored Cream

MELTING POINT.....N/A
SPECIFIC GRAVITY (Water=1)..0.93
VOLATILE BY VOLUME.. 77%
EVAPORATION RATE (Ethyl Ether=1)
Slower than Ethyl Ether
VOC... 448 grams/liter 3.75 lbs/gal

FIRE AND EXPLOSION DATA

FLASH POINT °F 107°F CC
FIRE EXTINGUISHING MEDIA CO₂, Dry Chemicals, Water Fog
SPECIAL FIRE FIGHTING PROCEDURES Fight like fuel oil fire. For large fires, firefighters use self-contained breathing apparatus.
UNUSUAL FIRE AND EXPLOSION HAZARD ... Closed containers exposed to high temperatures such as fire conditions may rupture.
FLAMMABLE LIMITS N/E

HEALTH HAZARD INFORMATION

THRESHOLD LIMIT VALUE N/E
HEALTH HAZARDS HARMFUL OR FATAL IF SWALLOWED!
IRRITANT WHEN IN CONTACT WITH EYES
AND OPEN OR ABRADED SKIN! Vapor
Harmful!
FIRST AID PROCEDURES:
SKIN CONTACT Wash with soap and excess water. Obtain medical attention if irritation occurs.
EYE CONTACT Flush promptly with excess water for 15 minutes.
IF SWALLOWED Call a physician.
INHALATION Do not induce vomiting. If conscious, give victim water to drink. Call a physician.
Remove from contaminated areas, apply artificial respiration if necessary.

State Regulations:

Trace amounts of ethylene oxide, a possible carcinogen, may be present in this product. The level does not constitute a significant risk.

CARCINOGENICITY:

IARC has concluded that there is "Sufficient Evidence for the carcinogenicity of crystalline silica to experimental animals" and "limited evidence" with respect to humans.

CALIFORNIA PROPOSITION 65:

Trace amounts of some chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm may be present in this product.

TOXICITY

ORAL (acute) (rats) N/E
INHALATION (acute) (rats) N/E
ACUTE INTRAPERITONEAL (mice) N/E
CHRONIC, SUBCHRONIC, ETC.: N/E

REACTIVITY DATA

STABILITY Stable
 INCOMPATIBILITY Strong acids and/or strong oxidizing agents (like Peroxides)
 HAZARDOUS DECOMPOSITION PRODUCTS Thermal decomposition will yield carbon monoxide and carbon dioxide and acrid fumes
 HAZARDOUS POLYMERIZATION Will not occur
 CONDITIONS TO AVOID Open flames, sparks, and high temperatures

SPILL AND DISPOSAL METHOD

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED Eliminate all sources of ignition. Cover spill with inert absorbents, like vermiculite or sand. Gather absorbed mass with non-sparking tools to clean containers for proper and prompt disposal. Wash area with detergent and water. Remove soiled clothing promptly and thoroughly clean and wash. Disposal method must comply with local, state, and federal regulations.

WASTE DISPOSAL METHOD

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION
 VENTILATION REQUIREMENTS
 LOCAL
 MECHANICAL
 SPECIAL
 EYE
 HAND
 OTHER PROTECTIVE EQUIPMENT
 Ventilate with air flow to keep vapor concentration below TLV. If room ventilation is lacking, use NIOSH approved respirator.
 Use in well-ventilated area
 Exhaust
 Acceptable
 See Handling and Storage Precautions
 Safety glasses
 Neoprene or equivalent required
 Eye wash fountain and safety shower should be available

HANDLING AND STORAGE PRECAUTIONS

OTHER STORAGE AND HANDLING
CONDITIONS

Keep away from extreme heat, open flame, or other sources of ignition. Do not store above 100°F. USE WITH ADEQUATE VENTILATION. DANGER: HARMFUL OR FATAL IF SWALLOWED! CONTAINS PETROLEUM DISTILLATES. COMBUSTIBLE! AVOID CONTACT WITH EYES! AVOID BREATHING OF VAPORS!

MISCELLANEOUS

HMIS RATING: Health = 2
Flammability = 2
Reactivity = 0
CODE: Least Hazardous = 0
Greatest Hazard = 4

Do not flame cut, weld, or melt empty containers.

PREPARED BY:
U.S. Chemical & Plastics
An Alco Industries Co

ADDRESS:
600 NOVA DRIVE SE
MASSILLON, OH 44646

PHONE: 330-830-6000

NOTES:

N/E = Not Established N/D = Not Determined N/A = Not Applicable

The information in this Material Safety Data Sheet has been compiled from our experience and data presented in various technical publications. It is the users responsibility to determine the suitability of this information for the adoption of safety precautions as necessary. We reserve the right to revise Material Safety Data Sheets from time to time as new technical information becomes available. The user has the responsibility to contact the Company to make sure that the sheet is the latest one issued.