


HWC G130, G132, G14



HARVEY WESTBURY CORP.

18 B East 5th Street
Paterson, NJ 07524
(973) 684-0800
Fax: (973) 684-8009

MATERIAL SAFETY DATA SHEET

Product Code: 40161, 40159, 40165,
40166, 40167 (HVW)
Trade Name: Royal Satin Liquid Wax
Synonym/Cross Reference: Polishing Wax, Liquid
Schedule B#: 3404.90.0000

Revision Date: 05/01/03
Supersedes Form: 02/25/97

HAZARDOUS INGREDIENTS

Materials/Components	% w/w	CAS No.	Hazard Data
Aliphatic Hydrocarbon	30-40%	64742-47-8	TLV100 ppm
Calcined Diatomaceous Earth	10-15%	91053-39-3	TLV 10 mg/m3 (As Dust) OSHA PEL 20ppm
Morpholine	1-5%	110-91-8	ACGIH: TLV 20ppm STEL 30ppm
Crystalline Silica (Cristobalite)	<3%	14464-46-1	OSHA: PEL .05mg/m3 Respirable
Crystalline Silica (Quartz)	<1%	14808-60-7	OSHA: PEL .1mg/m3 Respirable

PHYSICAL PROPERTIES

BOILING POINT:.....N/E
VAPOR PRESSURE.....N/E
VAPOR DENSITY (Air=1)...Heavier than air
WATER SOLUBILITY.: Insoluble but dispersible
APPEARANCE.....Brown

MELTING POINT.....A
SPECIFIC GRAVITY (Water=1)..98
VOLATILE BY VOLUME... Approx 70-80%
EVAPORATION RATE (Ethyl Ether=1)
Slower than Ethyl Ether
VOC.... 342 gms/ltr 2.86 lbs/gal

FIRE AND EXPLOSION DATA

FLASH POINT °F 110°F (Seta Closed Cup)
 FIRE EXTINGUISHING MEDIA CO₂, Dry Chemicals; Foam.
 SPECIAL FIRE FIGHTING PROCEDURES Firefighters wear self-contained breathing apparatus. Fight like a fuel oil fire.
 UNUSUAL FIRE AND EXPLOSION HAZARD Closed containers exposed to high temperatures such as fire conditions may rupture.
 FLAMMABLE LIMITS N/E

HEALTH HAZARD INFORMATION

THRESHOLD LIMIT VALUE N/E
 HEALTH HAZARDS Chronic overexposure to the components in this material can cause respiratory system, eyes, skin, kidney, central nervous system damage.

CALIFORNIA PROPOSITION 65:

Trace amounts of some chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm may be present in this product.

CARCINOGENICITY:

IARC has concluded that there is "sufficient evidence for the carcinogenicity of crystalline silica to experimental animals" and "limited evidence" with respect to humans.

FIRST AID PROCEDURES:

SKIN CONTACT Wash with soap and excess water. Obtain medical attention if irritation occurs.
 EYE CONTACT Flush promptly with excess water for 15 minutes.
 IF SWALLOWED Call a physician.
 INHALATION Do not induce vomiting. Call a physician. If conscious, give a glass of water to person. Remove from contaminated areas, apply artificial respiration if necessary, call a physician.

TOXICITY

ORAL (acute) (rats) N/E
 INHALATION (acute) (rats) N/E
 ACUTE INTRAPERITONEAL (mice) N/E
 CHRONIC, SUBCHRONIC, ETC.: N/E

REACTIVITY DATA

STABILITY Stable
INCOMPATIBILITY Strong acids or alkalies.
HAZARDOUS DECOMPOSITION PRODUCTS Thermal decomposition will yield carbon monoxide
and carbon dioxide.
HAZARDOUS POLYMERIZATION Will not occur.
CONDITIONS TO AVOID Open flames, sparks, and high temperatures.

SPILL AND DISPOSAL METHOD

STEPS TO BE TAKEN IF MATERIAL IS
RELEASED OR SPILLED Wash and clean up small spills with water and
detergent. Pick up large spills with inert absorbent
and place in a container for disposal.
WASTE DISPOSAL METHOD Dispose method must comply with local, state, and
federal regulations.

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION With general room ventilation does not require any
respiratory protection. If room ventilation is
lacking, use NIOSH approved respirator.
VENTILATION REQUIREMENTS General room ventilation.
LOCAL Exhaust
MECHANICAL Acceptable
SPECIAL None
EYE Safety glasses.
HAND Neoprene or equivalent.
OTHER PROTECTIVE EQUIPMENT Eye wash fountain and safety shower should be
available.

HANDLING AND STORAGE PRECAUTIONS

OTHER STORAGE AND HANDLING
CONDITIONS

MISCELLANEOUS

Keep away from extreme heat, open flames, or other sources of ignition. Store with adequate ventilation. Do not store above 100°F.

HMIS RATING: Health = 2

Flammability = 2

Reactivity = 0

CODE: Least Hazardous = 0

Greatest Hazard = 4

Do not flame cut, weld, or melt empty containers.

PREPARED BY:
U.S. Chemical & Plastics
An Alco Industries Co

ADDRESS:
600 Nova Drive SE
Massillon, OH 44646

PHONE: 330-830-6000

NOTES: N/E = Not Established N/D = Not Determined N/A = Not Applicable

The information in this Material Safety Data Sheet has been compiled from our experience and data presented in various technical publications. It is the users responsibility to determine the suitability of this information for the adoption of safety precautions as necessary. We reserve the right to revise Material Safety Data Sheets from time to time as new technical information becomes available. The user has the responsibility to contact the Company to make sure that the sheet is the latest one issued.