



HARVEY WESTBURY CORP.

18 B East 5th Street

Paterson, NJ 07524

(973) 684-0800

Fax: (973) 684-8009

MATERIAL SAFETY DATA SHEET

MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATION STANDARD,
29 CFR 1910.1200. STANDARD MUST BE CONSULTED FOR SPECIFIC REQUIREMENTS.

#

Manufacturer's Name:

Innovative Chemical Corporation

Prepared by:

LAB Supervisor (Revised) 1/21/2005

SECTION I - Identification

Trade name:

Garry's Ultra Fleet Heavy Duty Wax (SKUS G137, G138)

Product code:

ME-233A

DOT Class:

Unrestricted/Non-regulated

Health

1

Flammability

1

Reactivity

0

Chemical name:

Mixture.

Section II - Hazardous ingredients/identity information

HAZARDOUS COMPONENTS

OSHA PEL

ACGIH TLV

Hydrotreated Light Distillate
(Cas# 64742-47-8)

TWA 400 PPM

400 PPM

All other ingredients are considered non-hazardous per OSHA 29 CFR 1910.1200

SECTION III - Chemical characteristics

Boiling point: N/D	Specific gravity (H2O=1) 1.0
Vapor pressure (mm Hg) N/D	Melting point: N/A
Vapor density (air=1) >1	Evaporation rate (Butyl Acetate=1) <1
Solubility in water: Completely	% Solids: 17%
Weight (lb/gal): 8.41	pH: 9.07
Viscosity: SPINDLE 2 @ 20rpm 380 cps.	

Appearance and odor:

Semi-viscous tan liquid with a hydrocarbon odor.

SECTION IV: - Fire and explosion hazard data

Flash point (method used)	Flammable limits	LEL	UEL
Will not flash	N/A	N/A	N/A

Extinguishing media:

Dry chemical, CO2, Foam, and Water Fog.

Special fire fighting procedures:

Use of S.C.B.A. recommended. This product does not ignite readily. Intense heat may cause ignition.

Unusual Fire and Explosion Hazards:

None known

SECTION V - Reactivity data

Stability Stable	Condition to Avoid None known
Incompatibility (materials to avoid) Strong acids and Oxidizers	
Hazardous decomposition or byproducts: CO & CO2.	
Hazardous polymerization Will not occur	Conditions to avoid: None known

SECTION VI - Health hazard data

Acute health hazards:

None known

Chronic health hazards:

None known.

Carcinogenicity:

This product contains no substances or compound which are considered to be carcinogenic by OSHA, NTP, IARC or SARA Title III Section 313.

Signs and symptoms of exposure:

Eyes:

Irritation, redness & blurred vision

Dermal:

Irritation, defatting, redness

Inhalation:

May cause dizziness

Ingestion:

Nausea, vomiting & abdominal cramps

Emergency and first aid procedures.

Eyes

Flush with large amounts of water for 15 minutes. If irritation persists, get medical attention.

Dermal:

Wash with soap & water and rinse thoroughly

Inhalation:

Remove subject to fresh air and get medical attention.

Ingestion:

DO NOT INDUCE VOMITING.

Give conscious subject water to dilute. Seek medical attention.

SECTION VII - Precautions for safe handling and use:

Steps to be taken in case material is released or spilled:

PICK UP LARGE SPILLS FOR PROPER DISPOSAL.

SMALL SPILLS, WASH DOWN WITH WATER

Waste disposal method:

FOLLOW LOCAL, STATE AND FEDERAL REGULATIONS.

SECTION VIII - Control measures

Respiration protection (specify type) :
NIOSH approved in confined areas.

Ventilation
Good air circulation

Protective gloves
Vinyl or rubber

Eye protection
Splash protection

Other protective clothing or equipment:
As needed to prevent prolonged skin contact

Work/Hygenic practices:
Always wash hands and face before consuming food or beverages or using smoking materials

SECTION IX - NOTES: Note to Physician:

None

THE INFORMATION CONTAINED HERIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR RESULTS TO BE OBTAINED FROM THE USE THEREOF.

VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PARTY PERSONS PROXIMATELY CAUSED BY THE MATERIAL IF REASONABLE SAFETY PROCEDURES ARE NOT ADHERED TO AS STIPULATED IN THE DATA SHEET. ADDITIONALLY, VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PARTY PERSONS PROXIMATELY CAUSED BY ABNORMAL USE OF THE MATERIAL EVEN IF REASONABLE SAFETY PROCEDURES ARE FOLLOWED. FURTHERMORE, VENDEE ASSUMES THE RISK IN HIS USE OF THE MATERIAL.